
TECHNICAL DATA SHEET NO: W1**ACRYLSHIELD****100% Acrylic Exterior Finish**

PRODUCT DESCRIPTION

ACRYLSHIELD is a premium low sheen water-borne acrylic coating, which is formulated for exterior masonry application. ACRYLSHIELD is pigmented with light stable colorant that provides a smooth and highly decorative finishing with good durability and weathering properties against ultra violet degradation and fungus growth.

FEATURES/ TECHNICAL INFORMATION

Colour	Refer to Acrylshield 100% Acrylic Exterior Finish Paint colour card
Specific Gravity	Approximately 1.30
Finish	Low sheen
Flash Point	Non-flammable

TYPICAL/ RECOMMENDED USE

Acrylshield Plastic Dressing Emulsion is specially formulated for use on exterior concrete and masonry surfaces.

PRODUCT DATA/ PHYSICAL PROPERTIES

Recommended Dry film Thickness	30 - 40 microns
Drying Time (at 27°C)	Touch Dry : 15 - 30 minutes Hard Dry : 30 - 60 minutes
Recoating Interval	Min 1 hours
Theoretical Coverage	11 - 13 m ² / liter per coat
Surface Preparation	Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.

APPLICATION DATA

Application Method	Brush, roller or spray gun
Mixing Ratio (by volume)	The paint is ready for use after proper stirring. If thinning is required, add water may be added up to a max 5%
Thinner/ Cleaner	Water

SHIPPING DATA/ STORAGE & PACKAGING

Storage	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed.
Handling	Handle with care. Stir well before use.
Shelf life	12 months.
Packaging	5 & 20 liters

SAFETY PRECAUTION

- * This product is flammable. Keep away from sources of ignition. No smoking. Keep container tightly and keep out of reach of children.
 - * Wear suitable person protective clothing such as overall during painting. Ensure adequate ventilation. In case of insufficient ventilation during spraying, wear suitable respiratory equipment and eye protection goggle. Do not breathe
-

or inhale mist.

* Avoid skin and eye contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and seek medical immediately if discomfort persists.

DISCLAIMER

Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.
