

# FEDERAL PAINT (M) SDN BHD (797027-H)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang,  
68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876



Colour the earth since 1958

Website : [www.federalpaint.com.my](http://www.federalpaint.com.my)

Email : [enquiry@federalpaint.com.my](mailto:enquiry@federalpaint.com.my)

---

## TECHNICAL DATA SHEET NO: W5

### FEDESILK Superior Silky Interior Finish

---

**PRODUCT DESCRIPTION** Fedesilk is a premium modified acrylic wall finish with excellent flow and high smooth for interior application. It has excellent alkali, water and weather resistance.

---

#### FEATURES/ TECHNICAL INFORMATION

Colour	Refer to Fedesilk colour card
Specific Gravity	Approximately 1.40
Finish	Matt
Flash Point	Non-flammable

---

**TYPICAL/ RECOMMENDED USE** Fedesilk is suitable for interior concrete and masonry. Not recommended for areas subject to heavy or frequent condensation

---

#### PRODUCT DATA/ PHYSICAL PROPERTIES

Recommended Dry film Thickness	30 - 40 microns
Drying Time (at 27°C)	Touch Dry : 15 - 20 minutes Hard Dry : 1 hour
Recoating Interval	Min 1 hours
Theoretical Coverage	10 - 12 m <sup>2</sup> / liter per coat
Surface Preparation	Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.

---

#### APPLICATION DATA

Application Method	Brush, roller or spray gun
Mixing Ratio (by volume)	The paint is ready for use after proper stirring. If thinning is required water may be added up to a max of 5%
Thinner/ Cleaner	Water

---

#### SHIPPING DATA/ STORAGE & PACKAGING

Storage	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed.
Handling	Handle with care. Stir well before use.
Shelf life	12 months.
Packaging	5, 18 liters

---

#### SAFETY PRECAUTION

\* This product is flammable. Keep away from sources of ignition. No smoking. Keep container tightly and keep out of reach of children.  
\* Wear suitable person protective clothing such as overall during painting. Ensure adequate ventilation. In case of insufficient ventilation during spraying, wear suitable respiratory equipment and eye protection goggle. Do not breathe

---

or inhale mist.

\* Avoid skin and eye contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and seek medical immediately if discomfort persists.

---

**DISCLAIMER**

Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.

---