

**Technical Data Sheet No: W10****FELTEC ROOF GUARD  
Exterior Paint for Rooftiles**

<b>PRODUCT DESCRIPTION</b>	Federal Roof Guard is a high quality mid sheen water-borne acrylic coating, which is formulated for old and new roofs such as cement fibre sheets and unglazed roof tiles. Federal Roof Guard is pigmented with light stable colorant that provides a smooth and highly decorative finishing with good durability and weathering properties against ultra violet degradation and fungus growth.
<b>FEATURES</b>	: Dirt and U.V resistant. : Solvent free and environment friendly : Very good adhesion properties. : Algae and fungus resistant. : Easy and friendly in application. : Excellent flow and opacity.
<b>TYPICAL USES</b>	Federal Roof Guard is used as protective/decorative coating over old and new rooftiles.
<b>PRODUCT DATA</b>	Finish ..... mid sheen Color ..... few range Surfaces ..... Primed surfaces. Weight solids .....40% Viscosity .....80 K.U. pH ..... 8-9 Dry film thickness ..... Approx 35 to 50 micron No. of coats ..... 1 or 2 Theoretical coverage ..... Approx 10 m <sup>2</sup> /lit.  When computing actual coverage, allow for application losses, surface irregularities etc.
<b>APPLICATION</b>	Application ..... Brush/ Roller /Spray. Drying times @ 25 °C to touch ..... 30 minutes. to recoat ..... 2 hours Drying times are dependent on temperature and humidity. Thinner / Cleaner..... Clean Water
<b>SHIPPING DATA</b>	Shelf life ..... 12 months. Packaging .....5 & 20 liters. (For project use only)
<b>SAFETY PRECAUTION</b>	This product is not flammable. Ensure adequate ventilation during application.
<b>DISCLAIMER</b>	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.