
Technical Data Sheet No: S12**FELTEC WOODCOAT****Exterior Paint For Timber And Galvanized Substrates**

PRODUCT DESCRIPTION

FELTEC Woodcoat is a premium matt water-borne acrylic coating that is formulated for exterior application on woods. Feltec Woodcoat is pigmented with light stable pigments that provides a smooth and highly decorative finishing with good durability and weathering properties against ultra violet degradation and fungus growth.

FEATURES

: Dirt and U.V resistant.
 : Solvent free and environment friendly
 : Very good adhesion properties over wood substrates and galvanized iron sheets.
 : Algae and fungus resistant.
 : Easy and friendly in application.
 : Excellent flow and opacity.

TYPICAL USES

Feltec Woodcoat is used as finish coat over prepared wood and galvanized iron surfaces

PRODUCT DATA

Finish Matt
 Color few range
 Surfaces wood and galvanized iron surfaces.
 Weight solids 50%
 Viscosity 100 K.U.
 pH 8-9
 Dry film thickness Approx 35 to 50 micron
 No. of coats 1 or 2
 Theoretical coverage Approx 10 m²/lit.

When computing actual coverage, allow for application losses, surface irregularities etc.

APPLICATION

Application Brush/ Roller .
 Drying times @ 25 °C
 to touch 30 minutes.
 to recoat 2 hours
 Drying times are dependent on temperature and humidity.
 Thinner / Cleaner..... Clean Water

SHIPPING DATA

Shelf life 12 months.
 Packaging 1 & 5 liters.

SAFETY PRECAUTION

This product is not flammable.
 Ensure adequate ventilation during application.
 This product is for industrial use only.

DISCLAIMER

Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.