

FEDERAL PAINT (M) SDN BHD (797027-H)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang,
68000 Ampang, Selangor.
Tel : 03-4292 4684 Fax : 03-4291 5303

FEDERAL PAINT

Colour the earth since 1958

Website : www.federalpaint.com.my
Email : enquiry@federalpaint.com.my

TECHNICAL DATA SHEET NO: S2

FEDERAL GLO – 10 SYNTHETIC ENAMEL Synthetec Enamel Paint

PRODUCT DESCRIPTION Glo-10 Synthetic Enamel is fast dry alkyd enamel with high gloss finish. It is easy to apply and it forms a smooth, tough paint film, which has excellent gloss, fungus resistance and durability.

FEATURES/ TECHNICAL INFORMATION

Colour	Refer to Glo-10 colour card
Specific Gravity	Approximately 1.05
Finish	High gloss
Flash Point	About 35°C

TYPICAL/ RECOMMENDED USE Glo-10 Synthetic Enamel is suitable for use on all types of interior and exterior wood, properly primed metal and masonry surfaces.

PRODUCT DATA/ PHYSICAL PROPERTIES

Recommended Dry film Thickness	30 - 35 microns
Drying Time (at 27°C)	Touch Dry : 2 - 4 hours Hard Dry : 18 hours
Recoating Interval	Overnight
Theoretical Coverage	12 - 16 m ² / liter per coat
Surface Preparation	Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.

APPLICATION DATA

Application Method	Brush, roller or spray gun
Mixing Ratio (by volume)	The paint is ready for use after proper stirring. If thinning is required, add 5% of Federal thinner MO-464 for easy application.
Thinner/ Cleaner	Federal Thinner MO-464 or mineral Turpetine

SHIPPING DATA/ STORAGE & PACKAGING

Storage	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed.
Handling	Handle with care. Stir well before use.
Shelf life	12 months.
Packaging	1, 5 & 20 liters

SAFETY PRECAUTION

* This product is flammable. Keep away from sources of ignition. No smoking. Keep container tightly and keep out of reach of children.
* Wear suitable person protective clothing such as overall during painting. Ensure adequate ventilation. In case of insufficient ventilation during spraying, wear suitable respiratory equipment and eye protection goggle. Do not breathe

or inhale mist.

* Avoid skin and eye contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and seek medical immediately if discomfort persists.

DISCLAIMER

Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.
