

FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang,
68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876



Email: info@federalpaint.com.my

Website: federalpaint.com.my

TECHNICAL DATA SHEET NO: MW7

ROYALITE

Premium Interior Finish

PRODUCT DESCRIPTION	Royalite is a premium modified Vinyl acrylic wall finish with excellent flow and high smooth for interior application.
TECHNICAL INFORMATION Colour Specific Gravity Finish Flash Point	Refer to Royalite colour card Approximately 1.25 ~ 1.57 Matt Non-flammable
RECOMMENDED USE	Royalite is suitable for interior concrete and masonry. Not recommended for areas subject to heavy or frequent condensation
PRODUCT DATA Recommended Dry film Thickness Drying times Recoat Theoretical coverage	30 ~ 40 microns Touch Dry : 15 - 20 minutes Min : 1 hours 10 ~ 12 m ² / liter per coat
APPLICATION DATA Application Method Mixing Ratio (by volume) Thinner/cleaner Surface Preparation	Brush/ Roller/Spray Gun The paint is ready for use after proper stirring. If thinning is required, water may be added up to a max 5%. Water Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.
SHIPPING, STORAGE & PACKAGING Storage Handling Shelf life Packing Size	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed. Handle with care. Stir well before use. 12 months. 5 & 18 liters
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.

[FP02@03/13](#)