## FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office: 21, Persiaran Desa Ampang 1, Taman Sri Ampang,

68000 Ampang, Selangor.

Tel: 03-4292 4684 Fax: 03-4291 5303

Factory: Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel: 03-8737 8826 Fax: 03-8737 8876



Email: info@federalpaint.com.my Website: federalpaint.com.my

## **TECHNICAL DATA SHEET NO: FW11**

## **FELTEC VINYL FLOOR PAINT**

## **Durable Finish on Asbestos Roofing Tile & Cement Floor**

| PRODUCT DESCRIPTION            | Feltec Vinyl Floor Paint is top quality vinyl paint specially formulated                     |
|--------------------------------|--|
|                                | to provide excellent, durable and washable finish on asbestos roofing                        |
|                                | tile, cement floor, brickwork, hard and softboards.  |
|                                | and, certain most, priektions, maid and solubourder  |
| TECHNICAL INFORMATION          |  |
| Specific Gravity               | Approximately 1.20   |
| Finish                         | Low sheen  |
| Flash Point                    | Non-flammable  |
| RECOMMENDED USE                | Feltec Vinyl Floor Paint is designed for use on asbestos roofing tile,                       |
|                                | cement floor, brickwork, hard and soft boards. Best to apply Feltec                          |
|                                | Sealer 1011 (Solvent- based Sealer) if high moisture is present, prior to apply              |
|                                | this Feltec Vinyl Floor Paint.   |
| PRODUCT DATA                   |  |
| Recommended Dry film Thickness | 30 ~ 40 microns  |
| Drying times                   | Touch Dry : 30 minutes   |
|                                | Hard Dry : 1 hour  |
| Recoat                         | Min : 2 hours  |
| Theoretical coverage           | 9 ~ 10 m² / liter per coat   |
| Volume Solids                  | Approximately 35 %   |
| APPLICATION DATA               |  |
| Application Method             | Brush/ Roller/Spray Gun  |
| Mixing Ratio (by volume)       | The paint is ready for use after proper stirring. If thinning is required,                   |
|                                | water may be added up to a max 5%.   |
| Thinner/cleaner                | Water  |
| Surface Preparation            | Surfaces must be dry, clean, sound and free from any loose material,<br>dirt, grease or wax. |
|                                | uit, grease or wax.  |
| SHIPPING, STORAGE & PACKAGING  |  |
| Storage                        | The product should be kept in a cool and well ventilated place protected                     |
|                                | from direct sunlight. Container must be kept tightly closed.                                 |
| Handling                       | Handle with care. Stir well before use.  |
| Shelf life                     | 12 months.   |
| Packing Size                   | 5 liters   |
| DISCLAIMER                     | Federal Paint believes that the data contained herein are factual.                           |
|                                | The data are not to be taken as a warranty or representation for which                       |
|                                | Federal Paint assumes legal responsibility. We reserve the right to change                   |
|                                | the given data without notice.   |
| FD00@00/40                     |  |

FP02@03/13