Product Information

KRYSTAL AEROSOL PAINT



Introduction

KRYSTAL Aerosol Paint is a quick dry, high gloss, good hiding power, good color retention and CFC (halogen) free and Sulphur free aerosol paint suitable for use on metal surface.

Properties

Spray viscosity	: 12.0 – 14.0 seconds
Appearance	: 20.00 – 23.00 % (varies according to color)
Drying time	: 5 minutes (Touch dry) 10 minutes (Hard dry)

Application

- 1. Shake can vigorously for at least 30 seconds before use.
- 2. Hold can approximately 20 30 cm away from the substrate.
- 3. Spray uniform by moving the can horizontally from left to right.
- 4. Spray 2 3 thin coats for good results instead of one heavy coat.
- 5. Recoating interval is 5 10 minutes.
- 6. Before storing paint, clear the nozzle by turning can upside down and press actuator for approximately 2 seconds.

Precaution

- 1. Highly inflammable, keep away from heat, sparks and open flame.
- 2. Avoid skin or eye contact.
- 3. Keep out of reach of child.
- 4. Do not puncture or incinerate can.
- 5. Ensure adequate ventilation during use.

TDS/KAP/R1C4/OCT15

FEDERAL PAINTS MANUFACTURING (M) SDN. BHD. 199601009340 (381688-T) 21, Persiaran Desa Ampang 1, Taman Sri Ampang, 68000 Ampang, Selangor, Malaysia. Tel: 03-4292 4684

The above data are the results of carefully executed investigated. We do not guarantee the applicability or the accuracy of this information or suitability of our products in any given situation, because we cannot control the wide range of possibility. The products discussed are sold without warranty, either express or implied. We do not accept responsibility for damage of any kind.