

FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)



Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang, 68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876

Email: info@federalpaint.com.my

Website: federalpaint.com.my

TECHNICAL DATA SHEET

NO: FW7

FEDELITE PLUS

Premium Interior Matt Finish

PRODUCT DESCRIPTION	Fedelite Plus is an economy matt emulsion paint based on modified acrylic binder. It can be applied on interior surfaces like walls, ceilings, soft boards and masonry surfaces.										
TECHNICAL INFORMATION	<table> <tr> <td>Colour</td><td>Refer to Fedelite Plus colour card</td></tr> <tr> <td>Specific Gravity</td><td>Approximately 1.40 – 1.50</td></tr> <tr> <td>Finish</td><td>Matt Finish</td></tr> <tr> <td>Flash Point</td><td>Non-flammable</td></tr> </table>	Colour	Refer to Fedelite Plus colour card	Specific Gravity	Approximately 1.40 – 1.50	Finish	Matt Finish	Flash Point	Non-flammable		
Colour	Refer to Fedelite Plus colour card										
Specific Gravity	Approximately 1.40 – 1.50										
Finish	Matt Finish										
Flash Point	Non-flammable										
RECOMMENDED USE	Fedelite Plus is suitable for interior concrete and masonry. Not recommended for areas subject to heavy or frequent condensation.										
PRODUCT DATA	<table> <tr> <td>Recommended Dry film Thickness</td><td>30 ~ 40 micron per coat</td></tr> <tr> <td>Drying times</td><td>Touch Dry : 15 - 20 minutes</td></tr> <tr> <td>Recoat</td><td>Min : After 2 hours</td></tr> <tr> <td>Theoretical coverage</td><td>10 – 12 m² / liter per coat</td></tr> <tr> <td>Volume Solids</td><td>Approximately 35 %</td></tr> </table>	Recommended Dry film Thickness	30 ~ 40 micron per coat	Drying times	Touch Dry : 15 - 20 minutes	Recoat	Min : After 2 hours	Theoretical coverage	10 – 12 m ² / liter per coat	Volume Solids	Approximately 35 %
Recommended Dry film Thickness	30 ~ 40 micron per coat										
Drying times	Touch Dry : 15 - 20 minutes										
Recoat	Min : After 2 hours										
Theoretical coverage	10 – 12 m ² / liter per coat										
Volume Solids	Approximately 35 %										
APPLICATION DATA	<table> <tr> <td>Application Method</td><td>Brush/ Roller/Spray Gun application.</td></tr> <tr> <td>Mixing Ratio (by volume)</td><td>The paint is supplied ready for use. If thinning is required for the first coat, not more than 5% by volume of water may be added. Thinning is not recommended for subsequent coat.</td></tr> <tr> <td>Thinner/cleaner</td><td>Water</td></tr> <tr> <td>Surface Preparation</td><td>Surfaces to be painted should be thoroughly dry and clean, free from grease or wax, flake, chalk and dirt.</td></tr> </table>	Application Method	Brush/ Roller/Spray Gun application.	Mixing Ratio (by volume)	The paint is supplied ready for use. If thinning is required for the first coat, not more than 5% by volume of water may be added. Thinning is not recommended for subsequent coat.	Thinner/cleaner	Water	Surface Preparation	Surfaces to be painted should be thoroughly dry and clean, free from grease or wax, flake, chalk and dirt.		
Application Method	Brush/ Roller/Spray Gun application.										
Mixing Ratio (by volume)	The paint is supplied ready for use. If thinning is required for the first coat, not more than 5% by volume of water may be added. Thinning is not recommended for subsequent coat.										
Thinner/cleaner	Water										
Surface Preparation	Surfaces to be painted should be thoroughly dry and clean, free from grease or wax, flake, chalk and dirt.										
SHIPPING, STORAGE & PACKAGING	<table> <tr> <td>Storage</td><td>The product should be kept in a cool and well ventilated place protected from direct sunlight.</td></tr> <tr> <td>Handling</td><td>Handle with care. Stir well before use.</td></tr> <tr> <td>Shelf life</td><td>12 months.</td></tr> <tr> <td>Packing Size</td><td>1L, 7L and 18L</td></tr> </table>	Storage	The product should be kept in a cool and well ventilated place protected from direct sunlight.	Handling	Handle with care. Stir well before use.	Shelf life	12 months.	Packing Size	1L, 7L and 18L		
Storage	The product should be kept in a cool and well ventilated place protected from direct sunlight.										
Handling	Handle with care. Stir well before use.										
Shelf life	12 months.										
Packing Size	1L, 7L and 18L										
SAFETY PRECAUTION	<ol style="list-style-type: none"> Keep container tightly closed. Keep out of reach children or away from food and drink. Ensure good ventilation during application and drying. When applying paint, it is advisable to wear eye protection. In case of contact eyes rinse with plenty of water immediately and seek medical advice. Remove splashes from skin by using soap or water. Paint must always be stored in a cool place. When delivering paint, care must be taken. Always keep container in a secure upright. Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations. 										
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.										